



Phone : (02646) 253660  
Fax : (F) (02646) 253660  
7313/2 G.I.D.C. Ind. Estate,  
ANKLESHWAR - 393 002.,  
Dist. Bharuch. (Gujarat)  
E-mail : capricorn\_coatings@yahoo.co.in

## **LOIDKOTE – 9** **(FIRE RESISTIVE ANTI-ABRASION COATING)**

**LOIDKOTE – 9** Anti-Abrasion Coating is a water based fire resistive coating for the inner surface of cellular glass, polyurethane, rigid polyisocyanurate or urea-formaldehyde foam insulation to reduce abrasion from vibration and temperature changes of piping or vessels. Its strong adhesive qualities through a wide temperature range permit its use on extremely low temperature and dual temperature equipments.

### **TECHNICLE SPECIFICATION**

<b>Colour</b>	: Off White
<b>Specific Gravity</b>	: 1.40 to 1.50
<b>Average Non Volatile</b>	: 69% by weight
<b>Average Coverage</b>	: 3.15 sq meters with 0.2 mm wet film thickness/kg.
<b>Drying Time</b>	: Tough : 1 hour. Through : 3 hours
<b>Service Temperature Limits</b>	: - 85° C to 93° C
<b>Application</b>	: Brush or spray
<b>Solvent For Clean Up</b>	: wet: warm soapy water dry: mineral spirit
<b>Flammability</b>	: Wet – Non Flammable Dry – Fire Resistive

### **Important :**

Store and apply between 4°C to 38°C. Protect from freezing until dry.  
Stir well before use, do not dilute.