



Phone : (02646) 253660
Fax : (F) (02646) 253660
7313/2 G.I.D.C. Ind. Estate,
ANKLESHWAR - 393 002.,
Dist. Bharuch. (Gujarat)
E-mail : capricorn_coatings@yahoo.co.in

Loid Bond 87

A superior adhesive to adhere dense thermal insulation materials such as 85% magnesia, asbestos cloth, asbestos block to itself and non porous surfaces. After drying this adhesive forms a hard brittle incombustible film. Since the dry film is soluble in water it is advisable not to use Loid Bond – 87 where moisture ingresses.

TECHNICLE SPECIFICATION

Colour	: Light Grey
Viscosity	: Soft Paste
Specific Gravity	: 1.45
Average Non Volatile	: 53%
Average Coverage	: 1.25 Sq. meter per Kg.
Drying Time	: Bonding Time : 15 mts. Set Through : 8 hours
Service Temperature Limits	: 20 degree C to 350 degree C
Application	: Brush
Solvent For Clean Up	: Water
Flammability	: Wet – Non Flammable Dry - Incombustible

Temperature limits are at coated surface

Important :

1. Stir well before use.
2. Protect from freezing during storage.
3. It is not recommended for use with glass or mineral wool.
4. Do not use on painted surface.